

S300

TRADITIONAL Smart PINpad



Supermarkets



Fashion & Retail



Food & Beverage



CLASSIC



Powered by
Prolin



PCI 4
SRED





















3.5"
Display



Pole Stand
Option

SPECIFICATIONS

	Operating System	Prolin / PaxMe
	Processor	ARM11
	Memory	128MB Flash + 64MB DDR RAM
	Card Readers	Chip & PIN NFC Contactless Magnetic Stripe
	Cameras	No
	Display	3.5" TFT QVGA 240 * 320 Pixels Touch Screen
	Comms Configurations	1 RS232 1 Mini USB (optional) 1 Ethernet (optional)
	Battery	No
	Printer	No
	SIM / SAM	3 SAMs
	Positioning	No
	Keys / Buttons	15 Keys: Func 0~9 Alpha Enter Clear Cancel Back-Lighting
	Audio	1 Speaker
	Ports	Single Multi-Port Connector: 1 RS232 1 USB2.0 OTG 1 Ethernet
	Physical	167 * 81 * 50 mm, 290g
	Environmental	0°C ~ 50°C (32°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 10% ~ 93% Relative Humidity, Non-Condensing
	Accessories	PS200 Pole Stand
	Certifications	PCI PTS 4.x SRED EMV L1 & L2 EMV Contactless L1 Visa payWave MasterCard Contactless UPI qUICS Amex ExpressPay Discover D-PAS JCB J/Speedy Interac Flash MasterCard TQM Common.SECC UKCC CE RoHs

